



Howmet Fastening Systems

Phone: Sales +1 800 992 4444

Technical Support +1 310 784 6409

Email: HFSTechSupport@howmet.com

Website: www.hfs.howmet.com

Item # MF6001-04, MF6001 - Anchor Nut Miniature, Right Angle, Floating

THREAD: AS8879

MATERIAL:

- Nut - A286 corrosion resistant steel per AMS5525.
- Basket - 321 series corrosion resistant steel.

FINISH:

- Nut - Kaylube molybdenum disulfide dry lubricant coated per AS5272, Type I.
- Basket - Passivated per AMS2700.

PERFORMANCE: NASM25027.

FLOATABILITY: .020 min. radially from centered position.

TEMPERATURE: 450°F.

NOTES: "B" is maximum dimension when nut is fully floated.

Specifications

A - Max	0.684
B - MAX	0.344
C ± .002	0.219
D - MIN	0
E ± .005	0.170
H - MAX	0.153
J ± .005	0.325
K +.005 / -.000	0.098
M - MIN	0
P - REF	0.180
V - REF	0.025

W - MAX	0.325
Approx. Weight (LBS/100)	0.30
Thread Type	Unified
Configuration 1	Right Angle
Configuration 2	Floating
Configuration 3	Miniature
Lock	Crimp Lock
Simplified Material	CRES
Strength	125KSI - 900Mpa
Temperature	450°F - 235°C
Thread	0.1120-40 UNJC-3B