

SECTION A-A


TABLE 1

PART NUMBER	MATERIAL	HEAT TREATMENT	FINISH	MOUNTING TYPE	D DIA
312-12	CARBON STEEL, PER ASTM A684, 1040, OR 1050	166 KSI MIN	CADMIUM PLATE PER QQ-P-416, TYPE II, CLASS 2	RIVET	.096-.102
312-12A	CRES, PER ASTM A240, CLASS 305,	NONE	PASSIVATE PER MIL-S-5002	RIVET	.128-.134
312-12B	CARBON STEEL, PER ASTM A684, 1040, OR 1050	166 KSI MIN	ZINC PLATE PER ASTM B633, TYPE II, CLASS 8, (YELLOW)	RIVET	.096-.102
312-12S	CRES, PER ASTM A240, CLASS 305	NONE	PASSIVATE PER MIL-S-5002	RIVET	.096-.102
312-12W	CARBON STEEL, PER ASTM A684, 1040, OR 1050	166 KSI MIN	OIL COATED	SPOTWELD	NONE
312-12WS	CRES, PER ASTM A240 CLASS 305	NONE	PASSIVATE PER MIL-S-5002	SPOTWELD	NONE

NOTES; UNLESS OTHERWISE SPECIFIED:

- FOR INSTALLATION PROCEDURE, SEE CAMLOC DWG 26F1 & CAMLOC CATALOG.
- PARTS PRODUCED PRIOR TO FEBRUARY 1, 1999 USABLE TO STOCK DEPLETION, HOWEVER ONLY PARTS MANUFACTURED AFTER FEBRUARY 1, 1999 MAY BE CROSS REFERENCED TO ANY CUSTOMER PART NUMBER.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES & PER ANSI Y14.5M-82 TOLERANCES:  
 ANGLES = ±1°  
 FRACTIONS = ±1/32  
 DECIMALS .XX = ±.02  
 .XXX = ±.010

APPROVED DATE	 <b>AEROSPACE FASTENER DIVISION</b> 3012 WEST LOMITA BOULEVARD TORRANCE, CA 90505	CAGE CODE <b>71286</b> CAMLOC PRODUCT
1 FEB 99		
REV. LETTER AND DATE		
R 28 APR 04	RECEPTACLE SHEET METAL	312-12 SHEET 1 OF 1
DAF NUMBER		
DAF 62739		

S44187