



**PART NO. CALLOUT:
40R39-1-()**

SUFFIX	MATERIAL			FINISH	WEIGHT LBS/100
	INSERT	CLIP	SPRING		
1AA	ZINC BASE ALLOY DIE CASTING PER ASTM B86	CARBON STEEL PER QQ-S-700	MUSIC WIRE PER ASTM A228	ZINC PLATED PER ASTM B633, CLASS 5, TYPE II (YELLOW CHROMATE)	1.91
1AB				ZINC PLATED PER ASTM B633, CLASS 5, TYPE III (CLEAR CHROMATE)	

NOTES: UNLESS OTHERWISE SPECIFIED.

1. WHEN SELECTING STUD LENGTH DASH NO. TO BE USED WITH THIS RECEPTACLE, ADD .020 (RECEPTACLE TAB THICKNESS) TO TOTAL GRIP, "G" & SELECT DASH NO. FROM 214-16 RECEPTACLE COLUMN IN STANDARD 4002 SERIES STUD LENGTH SELECTION CHART.

<2> THIS RECEPTACLE IS INSTALLED IN A RECTANGULAR HOLE .562-.570 WIDE x .874-.882 LONG, IN INNER FRAME. MATERIAL THICKNESSES UP TO .150.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES & PER ANSI Y14.5M-82 TOLERANCES:

ANGLES = ±1°
FRACTIONS = ±1/32
DECIMALS .XX = ±.02
 .XXX = ±.010

APPROVED DATE	22 JAN 98
REV. LETTER AND DATE	H 23 MAY 00
DAF NUMBER	DAF 47933

Fairchild AEROSPACE FASTENER DIVISION
3012 WEST LOMITA BOULEVARD
TORRANCE, CA 90505

CAGE CODE **71286**
CAMLOC PRODUCT

**RECEPTACLE ASSEMBLY
CLIP-IN, SINGLE HOLE MOUNT**

40R39

SHEET 1 OF 1

S44954