

Huck Blind Bolt Part Number Cross Reference



A286 CRES Blind Bolts at 95 KSI Shear Strength

| Huck Part Numbers (Nominal Diameter) | MS Part Numbers (Nominal Diameter) | Description | Huck Part Numbers (Oversize Diameter) |
|---|------------------------------------|--|---------------------------------------|
| B100-EU05 & EU06 (100° Flush Head) | MS21140-05 & - 06 | Double Action Tool Installation Method Only | OB100-EU05 & EU06 |
| B100-EU08 to EU16 (100° Flush Head) | MS21140-08 to -12 | Single Action Installation Method with Shear Cap collars | OB100-EU08 to EU12 |
| SB100-EU05 & EU06 (100° Flush Head) | MS21140S05 & S06 | Single Action Installation Method with Shear Cap collars | OSB100-EU05 & EU06 |
| UB100-EU05 to EU12 (1) (100° Flush Head) | MS21140U05 to U12 (1) | Single Action Installation Method (UNIMATIC® Blind Bolt) | OUB100-EU8 to EU12 |
| BP-EU05 & EU06 (Protruding Head) | MS21141-05 & - 06 | Double Action Tool Installation Method Only | OBP-EU05 & EU06 |
| BP-EU08 to EU16 (Protruding Head) | MS21141-08 to -12 | Single Action Installation Method with Shear Cap collars | OBP-EU08 to EU12 |
| SBP-EU05 & EU06 (Protruding Head) | MS21141S05 & S06 | Single Action Installation Method with Shear Cap collars | OSBP-EU05 & EU06 |
| UBP-EU05 to EU12 (1) (Protruding Head) | MS21141U05 to U12 (1) | Single Action Installation Method (UNIMATIC® Blind Bolt) | OUBP-EU8 to EU12 |

Note: (1) Part numbers followed with the letter "W" indicates installation with blunt nose long life installation tool.

© 2020 Howmet Aerospace Inc.