

PART NUMBER	A	B	C	D	E	F
CA21062-06-T10	.045	.062	.19 REF.	.06 REF.	.104	.138
CA21062-08-T10	.045	.062	.19 REF.	.09 REF.	.140	.187
CA21062-10-T10	.045	.078	.19 REF.	.11 REF.	.166	.228
CA21062-4-T10	.045	.078	.19 REF.	.15 REF.	.213	.309

NOTES:

1. MATERIAL: 17-4 CRES. PER AMS 5643
2. HEAT TREAT: COND. H-900 PER MIL-H-6875.
3. FINISH: GLASS BEAD BLAST AND PASSIVATE PER QQ-P-35.
4. THIS TOOL IS FOR USE WITH A CA21062-[]-R RETAINING RING AND CA21062-[]-[]-[], CA21063-[]-[]-[] OR CA21088-[]-[]-[] SCREWS.
SEE SHEET 2 FOR TOOL USAGE PROCEDURE.

DRAWING PROVIDES FORM, FIT AND FUNCTION DATA. DO NOT ATTEMPT TO MANUFACTURE PRODUCT USING THIS DRAWING.

DRAWN BY <i>G. JENSEN</i>	DATE 6-11-79
MP <i>[Signature]</i>	DATE 6-11-79
APPROVED BY <i>RCW</i>	DATE 6-11-79
APPROVED BY	DATE
PROJECT NUMBER 76-098	

TITLE
**INSTALLATION TOOL
SPLIT RETAINING RING**

UNLESS OTHERWISE SPECIFIED
TOLERANCES
DECIMALS XX ± .02
XXX ± .010
ANGLES: ± 2°

MILLIMETERS
± 0.50
± 0.25


SURFACE FINISH
125 MICROINCHES



CA21062-33-T10

FSC: 29372 SHEET 1 OF 2

REVISION: B
C
D
E
F
G
H
I
J
K
L
M
N
O
P
Q
R
S
T
U
V
W
X
Y
Z
AA
AB
AC
AD
AE
AF
AG
AH
AI
AJ
AK
AL
AM
AN
AO
AP
AQ
AR
AS
AT
AU
AV
AW
AX
AY
AZ
BA
BB
BC
BD
BE
BF
BG
BH
BI
BJ
BK
BL
BM
BN
BO
BP
BQ
BR
BS
BT
BU
BV
BW
BX
BY
BZ
CA
CB
CC
CD
CE
CF
CG
CH
CI
CJ
CK
CL
CM
CN
CO
CP
CQ
CR
CS
CT
CU
CV
CW
CX
CY
CZ
DA
DB
DC
DD
DE
DF
DG
DH
DI
DJ
DK
DL
DM
DN
DO
DP
DQ
DR
DS
DT
DU
DV
DW
DX
DY
DZ
EA
EB
EC
ED
EE
EF
EG
EH
EI
EJ
EK
EL
EM
EN
EO
EP
EQ
ER
ES
ET
EU
EV
EW
EX
EY
EZ
FA
FB
FC
FD
FE
FF
FG
FH
FI
FJ
FK
FL
FM
FN
FO
FP
FQ
FR
FS
FT
FU
FV
FW
FX
FY
FZ
GA
GB
GC
GD
GE
GF
GG
GH
GI
GJ
GK
GL
GM
GN
GO
GP
GQ
GR
GS
GT
GU
GV
GW
GX
GY
GZ
HA
HB
HC
HD
HE
HF
HG
HH
HI
HJ
HK
HL
HM
HN
HO
HP
HQ
HR
HS
HT
HU
HV
HW
HX
HY
HZ
IA
IB
IC
ID
IE
IF
IG
IH
II
IJ
IK
IL
IM
IN
IO
IP
IQ
IR
IS
IT
IU
IV
IW
IX
IY
IZ
JA
JB
JC
JD
JE
JF
JG
JH
JI
JJ
JK
JL
JM
JN
JO
JP
JQ
JR
JS
JT
JU
JV
JW
JX
JY
JZ
KA
KB
KC
KD
KE
KF
KG
KH
KI
KJ
KK
KL
KM
KN
KO
KP
KQ
KR
KS
KT
KU
KV
KW
KX
KY
KZ
LA
LB
LC
LD
LE
LF
LG
LH
LI
LJ
LK
LL
LM
LN
LO
LP
LQ
LR
LS
LT
LU
LV
LW
LX
LY
LZ
MA
MB
MC
MD
ME
MF
MG
MH
MI
MJ
MK
ML
MN
MO
MP
MQ
MR
MS
MT
MU
MV
MW
MX
MY
MZ
NA
NB
NC
ND
NE
NF
NG
NH
NI
NJ
NK
NL
NM
NN
NO
NP
NQ
NR
NS
NT
NU
NV
NW
NX
NY
NZ
OA
OB
OC
OD
OE
OF
OG
OH
OI
OJ
OK
OL
OM
ON
OO
OP
OQ
OR
OS
OT
OU
OV
OW
OX
OY
OZ
PA
PB
PC
PD
PE
PF
PG
PH
PI
PJ
PK
PL
PM
PN
PO
PP
PQ
PR
PS
PT
PU
PV
PW
PX
PY
PZ
QA
QB
QC
QD
QE
QF
QG
QH
QI
QJ
QK
QL
QM
QN
QO
QP
QQ
QR
QS
QT
QU
QV
QW
QX
QY
QZ
RA
RB
RC
RD
RE
RF
RG
RH
RI
RJ
RK
RL
RM
RN
RO
RP
RQ
RR
RS
RT
RU
RV
RW
RX
RY
RZ
SA
SB
SC
SD
SE
SF
SG
SH
SI
SJ
SK
SL
SM
SN
SO
SP
SQ
SR
SS
ST
SU
SV
SW
SX
SY
SZ
TA
TB
TC
TD
TE
TF
TG
TH
TI
TJ
TK
TL
TM
TN
TO
TP
TQ
TR
TS
TT
TU
TV
TW
TX
TY
TZ
UA
UB
UC
UD
UE
UF
UG
UH
UI
UJ
UK
UL
UM
UN
UO
UP
UQ
UR
US
UT
UU
UV
UW
UX
UY
UZ
VA
VB
VC
VD
VE
VF
VG
VH
VI
VJ
VK
VL
VM
VN
VO
VP
VQ
VR
VS
VT
VU
VV
VW
VX
VY
VZ
WA
WB
WC
WD
WE
WF
WG
WH
WI
WJ
WK
WL
WM
WN
WO
WP
WQ
WR
WS
WT
WU
WV
WW
WX
WY
WZ
XA
XB
XC
XD
XE
XF
XG
XH
XI
XJ
XK
XL
XM
XN
XO
XP
XQ
XR
XS
XT
XU
XV
XW
XX
XY
XZ
YA
YB
YC
YD
YE
YF
YG
YH
YI
YJ
YK
YL
YM
YN
YO
YP
YQ
YR
YS
YT
YU
YV
YW
YX
YZ
ZA
ZB
ZC
ZD
ZE
ZF
ZG
ZH
ZI
ZJ
ZK
ZL
ZM
ZN
ZO
ZP
ZQ
ZR
ZS
ZT
ZU
ZV
ZW
ZX
ZY
ZZ



REVISION A 5-23-78 RLW B 8-28-78 RLW C 6-11-79 RLW D 8-28-84 DMJ

DRAWN BY <i>GL</i>	DATE 1-19-79	TITLE INSTALLATION TOOL SPLIT RETAINING RING	
MFG ENGRG <i>1-P</i>	DATE 1-26-78		
APPROVED BY <i>RLW</i>	DATE 1-24-78		
APPROVED BY <i>GP</i>	DATE 1-25-78		
PROJECT NUMBER 76098	UNLESS OTHERWISE SPECIFIED TOLERANCES DECIMALS XX ± 02 XXX ± 010 ANGLES ± 2°	MILLIMETERS ± 0.50 ± 0.25	SURFACE FINISH 125 MICROMETERS

Tridair

© Bunker Company
3078 W. Loma Blvd.
Torrance, CA 90505
213-538-2228

CA21062-□□-T10

FSC: 29372 SHEET 2 OF 2