


4002 Series. Grommets (continued)

Data Tables for Flared Retained Grommets.

("P", "L" and Grommet Dash Numbers)

To Select Grommet Dash Number

1. Determine "P" panel thickness.
2. Locate "P" thickness in the appropriate table below.
3. Find the corresponding dash number to the right.



Typical Installation
(for detail See Page A-57).

A

DATA TABLE 1		
P Panel Thickness	L	Grommet Length Dash Number
.040-.069	.109-.116	-040
.070-.099	.142-.149	-070
.100-.129	.172-.179	-100
.130-.159	.202-.209	-130
.160-.189	.232-.239	-160
.190-.219	.262-.269	-190

DATA TABLE 2		
P Panel Thickness	L	Grommet Length Dash Number
.040-.069	.155-.166	-140
.070-.099	.145-.156	-070
.100-.129	.165-.176	-100
.130-.159	.193-.204	-130
.160-.189	.220-.231	-160
.190-.219	.250-.261	-190

Notes: 1. For longer lengths contact Camloc Products Division.

2. Data tables are applicable to specific part numbers. Select the correct table as indicated on Page A-52.

See Grommet Weights on Page A-63.

DATA TABLE 3		
P Panel Thickness	L	Grommet Length Dash Number
.156-.219	.266-.296	-187
.220-.281	.328-.358	-250
.282-.343	.391-.421	-312
.344-.407	.453-.483	-375
.368-.432	.478-.508	-400
.405-.469	.516-.546	-437
.468-.532	.587-.608	-500
.593-.657	.703-.733	-625
.718-.782	.828-.858	-750
.780-.844	.891-.921	-812
.843-.907	.953-.983	-875
.968-1.032	1.078-1.108	-1000
1.030-1.094	1.141-1.171	-1062
1.093-1.157	1.203-1.233	-1125
1.218-1.282	1.328-1.358	-1250
1.343-1.407	1.453-1.433	-1375
1.468-1.532	1.578-1.608	-1500

How to Order:

Example:

"P" thickness = .125 inch.

Grommet selected: 40G15-[]S

From data above, Table #2 applies.

Grommet Dash Number selected from Table #2: -100.

Complete part number: 40G15-100S.